

**AMSOIL XL (7500) Series Motor Oils  
Beat the Competition Hands Down**

<b>TYPICAL TECHNICAL PROPERTIES (Revised as of 1/06)</b>	<b>AMSOIL XLF 5W-30 SYNTHETIC MOTOR OIL</b>	<b>MOBIL 1 5W-30 SUPER SYN MOTOR OIL</b>
Viscosity Index (ASTM D-2270)	173	169
Flash Point °C (°F) (ASTM D-92)	234 (453)	230 (446)
Fire Point °C (°F) (ASTM D-92)	246 (475)	235 (455)
Pour Point °C (°F) (ASTM D-97)	-43 (-45)	-48 (-54)
Noack Volatility, % weight loss (g/100g) (ASTM D-5800)	8.9	9.17
High Temperature/High Shear Viscosity @ 150°C and 1.0 X 10 <sup>6</sup> s <sup>-1</sup> , cP (ASTM D-4683)	3.20	3.09
Four Ball Wear Test @ 40 kgf, 75°C, 1200 rpm, 1 hour, scar diameter, mm (ASTM D-4172)	0.43	0.60
Total Base Number (ASTM D-2896)	9	8.45

**Just look at that Four Ball Wear Test. WOW!**

**Would your customers be interested  
in an oil this good?**